

Because Lives, Property and Businesses aren't Fireproof.



STI Series Stopper II

Harrington Signal Inc.
2519 4th Avenue, Moline, Illinois 61265
P.O. Box 590, Moline, Illinois 61266-0590
Direct: (800) 577-5758 Phone: (309) 762-0731 Fax: (309) 762-8215
Internet: www.harringtonfire.com



FEATURES

- Fits virtually all manual pull stations. Larger sizes and surface mounted pull stations accommodated with STI 3100 Conduit spacer (order separately).
- Tested and accepted by fire prevention authorities and approved by testing organizations.
- Cover is UV stabilized against sun deterioration.
- Available in red (blue, green or yellow as special order).
- Custom labeling available as special order.
- Unconditional lifetime guarantee of the Stopper II molded polycarbonate cover against breakage and damage.

- Can be used as a guard against physical damage to a manual pull station . . . with or without a warning horn.
- Weather resistant gaskets available. UL requires stations to be listed for outdoor use with cover.
- Power source is a 9 VDC alkaline battery on standard Stopper II. (Separate powered 24Vdc unit is available).

DESCRIPTION

This unique and patented device has been helping stop false fire alarms without restricting legitimate alarms for more than a decade. Use proven in virtually every kind of public building around the world, Stopper II can dramatically reduce or in some cases even eliminate false fire alarms. It is available in



STI Series

many different models, with or without warning horn, for flush or surface mounting, and with remote power relay output capability. Stopper II may be ordered in red (green, yellow or blue with custom labeling as special order) for specialized applications.

Ordering Information

| Model Number | Part Number | Description |
|---|-------------|---|
| STI1100** | 238-0109 | With horn for flush mounting, 9Vdc |
| STI1130 ** | 238-0118 | With horn and 2" spacer for surface mounting, 9Vdc |
| STI1200 | 238-0119 | Without horn for flush mounting |
| STI1230 | 238-0120 | Without horn, with 2" spacer for surface mounting |
| STI1100R* | 238-0138 | With horn for flush mounting, requires 24Vdc for operation |
| STI1130R* | 238-0139 | Surface mounted version of the 1100R, includes 2" conduit spacer |
| STI1100C9* | 238-0149 | With horn and contact, 9Vdc, flush mount |
| STI1130C9* | 238-0151 | Surface mounted version of the 1100C9. Includes conduit spacer |
| STI1100RC* | 238-0148 | With horn and relay contact, requires 24Vdc for operation, for flush mounting |
| STI1130RC* | 238-0150 | Surface mounted version of the 1100RC. Includes conduit spacer |
| * These models not tested with UL or other listing agencies ** These models listed with FM | | |
| Accessories for Above | | |
| STI-3002 | 238-0147 | Weather proof gasket4 |
| STI-3003 | 238-0152 | Neoprene weather proof conduit gasket (1/2" pipe) |
| STI-3004 | 238-0153 | Neoprene weather proof conduit gasket (3/4" pipe) |
| STI-3100 | 238-0136 | Conduit spacer, clear, 2" |

